








TraceTek® Leak Detection

ACCESSOIRES TT3000 - TT5000(HUV) - TT5001(HUV) - TT7000

TraceTek Products for Industrial and Environmental Applications

Product	Catalog No.	Selection	Description
TraceTek Components			
End termination 	TT-MET-MC	Modular end termination (with metal connector)	Terminates sensing circuit; has pin-type metal connector. Required at end of sensing circuit and ends of all branches.
Branching connector 	TT-MBC-MC	Modular branching connector (with metal connectors)	Allows a “T” or branch in the sensing circuit. Has pin-type connector to connect to cable from alarm module, two socket-type connectors to connect branches. Wires the branches in series and adds a simulated length of 15 ft on each branch to make clear division between areas.
Weighted length 	TT-WL-4.5M/15FT-MC	Weighted length (with plastic connectors)	Simulates 15 ft (4.5 m) of sensing cable. Makes a clear division between separate areas in a locating system.
Jumper Cables			
Modular leader cable 	TT-MLC-MC	Modular leader cable (with metal connector) Length: 12 ft (3.5 m)	Cable with one end prepared for connection to terminals in module (or for splicing to bulk jumper cable), and with socket-type metal connector at other end. Includes connector oversleeve.
Modular jumper cable 	TT-MJC-x-MC TT-MJC-1M/3FT-MC TT-MJC-3M/10FT-MC TT-MJC-7.5M/25FT-MC TT-MJC-15M/50FT-MC TT-MJC-30M/100FT-MC	Modular jumper cable 1 m 3 ft 3 m 10 ft 7.5 m 25 ft 15 m 50 ft 30 m 100 ft	Jumper cable in modular lengths with pin-type metal connector at one end, socket-type metal connector at other end. Includes connector oversleeve (heat-shrinkable tube) to protect connector after installation.